



图号/DWG NO.	86HB105-D1232-001
------------	-------------------



步 距 角/STEP ANGLE	1.2° ±5%
相 数/NO. OF PHASES	3
额定电压/RATED VOLTAGE	3.3V
额定电流/RATED CURRENT	3.0A
电 阻/RESISTANCE	1.1ohm±10% AT25℃
电 感/INDUCTANCE	4.5mH±20% AT 1kHz, 1Vrms
保持力矩/HOLDING TORQUE	4.3N. m
运行力矩/(AT —PPS) RUNNING TORQUE(AT —PPS)	——以上/MIN (——V. DC, ——A/相(PHASE), ——相励磁/EX)
绝缘耐压/DIELECTRIC STRENGTH	500V A.C 1分钟/MINUTE
绝缘电阻/INSULATION RESISTANCE	100MΩ 以上/MIN.
绝缘等级/INSULATION CLASS	CLASS B
温度上升/TEMPERATURE RISE	80K MAX.
转子惯量/ROTOR INERTIA	2500g. cm ²
重 量/WEIGHT	约/APPROX. 3250克/g
运行环境温度/OPERATION AMBIENT TEMP.	-20℃——+50℃
运行环境湿度/OPERATION AMBIENT HUM.	15%——90%

已受控

CONFIRMED&ACCEPTED BY CUSTOMER (客户确认&接受)									
COMPANY CHOP&SIGNATURE (盖章&签名)									
一般公差 TOLERANCE	±0.3/±3°	版本 REV.	年 月 日 DATE	变更番号 ECR NO.	变 更 内 容 REVISIONS		设计 BY	备注 NOTE	REV. A
设计/DESIGNED		比例 SCALE			型 号/MODEL 86BM40			三 维 图 THIRD ANGL PROJECTION	
审核/CHECKED		单位 UNIT		mm					
深圳锐特机电技术有限公司								页 SHEET	1/1